

# Dynafile® Contact Arms

## 4" to 14" Workable Reach



To maximize the life of 1/4" bearings or smaller, lower the operating air pressure to 45 PSIG (3.1 Bar) and run the motor at a lower RPM.

| Part Number  | Comments   | Belt Size (W x L)  | Contact Wheel Assembly (includes bearing and shaft)  | Platen Pad         |
|--|--|--|--|--------------------|
| 11178, 11179, 11257<br>         | <ul style="list-style-type: none"> <li>Up to 32" reach</li> <li>Enter slots as narrow as 3/8"</li> <li>Deburr 1/2" to 1" tubing</li> </ul>         | 11178:<br>1/2" x 34"<br>(9" reach with 5/16" dia. steel contact wheel)<br>11179:<br>1/2" x 34"<br>(9" reach with 5/8" dia. rubber contact wheel) | 11178:<br>11068 Wheel<br>(5/16" dia. steel)<br><br>11179:<br>11078 Wheel<br>(5/8" dia. rubber) | None               |
| 11257: Custom-made. Specify length and contact wheel.  |  |  |  |                    |
| 11212<br>                       | <ul style="list-style-type: none"> <li><b>45 PSIG maximum</b></li> <li>File round openings as small as 7/16"</li> </ul>                            | 1/4" x 24"   | 11066<br>5/16" dia. x 1/8" wide, steel   | 11034<br>1/4" wide |
| 11213<br>                       | <ul style="list-style-type: none"> <li><b>45 PSIG maximum</b></li> <li>See 11239 for heavy-duty version</li> </ul>                                 | 1/2" x 24"   | 11068<br>5/16" dia. x 3/8" wide, steel   | 11027<br>1/2" wide |
| 11214<br>                       | <ul style="list-style-type: none"> <li><b>45 PSIG maximum</b></li> <li>Work on contact wheel or platen pad</li> </ul>                              | 1/2" x 24"   | 11070<br>7/16" dia. x 3/8" wide, rubber  | 11025<br>1/2" wide |
| 11215<br>                     | <ul style="list-style-type: none"> <li>Enter 1/2" x 1/2" openings</li> </ul>   | 1/4" x 24"   | 11072<br>7/16" dia. x 1/8" wide, brass   | 11034<br>1/4" wide |
| 11216<br>                     | <ul style="list-style-type: none"> <li>Enter 5/16" x 3/4" openings</li> </ul>  | 1/4" x 24"   | 11074<br>5/8" dia. x 1/8" wide, rubber   | 11032<br>1/4" wide |
| 11217<br>                     | <ul style="list-style-type: none"> <li>Enter channels as narrow as 9/16"</li> </ul>  | 1/2" x 24"   | 11076<br>7/16" dia. x 3/8" wide, steel   | 11027<br>1/2" wide |
| 11218<br>                     | <ul style="list-style-type: none"> <li>Standard arm on Model 14000</li> <li>See 11228 for heavy-duty version</li> </ul>                            | 1/2" x 24"   | 11078<br>5/8" dia. x 3/8" wide, rubber   | 11025<br>1/2" wide |
| 11219<br>                     | <ul style="list-style-type: none"> <li>No platen due to offset design</li> <li>Ideal for slack polishing; also grinding radiuses</li> </ul>        | 1/4" or 2" x 24"   | 11080<br>1" dia. x 3/8" wide, radiused rubber  | None               |
| 11228<br>                     | <ul style="list-style-type: none"> <li>Heavy-duty steel</li> <li>Optional 11028 Steel Platen available for grinding</li> </ul>                     | 1/2" x 24"   | 11078<br>5/8" dia. x 3/8" wide, rubber   | 11025<br>1/2" wide |
| 11231<br>                     | <ul style="list-style-type: none"> <li>See 11243 for heavy-duty version</li> </ul>   | 1/2" x 24"   | 11084<br>3/4" dia. x 1/2" wide, rubber   | 11135<br>1/2" wide |
| 11232<br>"V" Shaped Wheel<br> | <ul style="list-style-type: none"> <li>For 1/8" wide belts</li> <li>No platen due to offset design</li> <li>Grind corners, strap polish</li> </ul> | 1/8" or 1/4" x 24"   | 11086<br>1" dia. x 3/8" wide, tapered urethane   | None               |